

UNIQUE CHAMFERING AND CUTTING ELECTRODE FOR ALL METALS.

SPECIAL FEATURES



- SPECIAL COATING CREATES 25% MORE "ARC BLAST FORCE.
- ELECTRICALLY CONDUCIVE "CUP" FOR EASE OF RESTRIKE.
- CAN ALSO BE USED FOR ALUMINIUM AND COPPER.
- SPECIFICALLY DESIGNED FOR SMALL 'AC' MACHINES.
- NO OVERHEATING OF ELECTRODE

APPLICATIONS

- Can gouge, bevel or cut all metals including stainless steels, alumiums and copper.
- Excellent for removal of stainless steel joints and overlays.

GOUGING RATES for CG 00

Diameter (mm)	Length (mm)	Arc Time of Gouging SEC/in (mm)	Weight of Gouged Metal g/min	Amperage Setting
3/32 (2.5)	14" (350)	1.6 (.064)	35	160
1/8 (3.2)	14" (350)	1.2 (.048)	100	230
5/32 (4.0)	14" (350)	1.0 (.04)	120	310
3/16 (5.0)	14" (350)	.8 (.032)	180	420

INTERNATIONAL SPECIFICATIONS

NONE - FINALLOY CG 00 IS A PROPRIETORY PRODUCT



WELD METAL ANALYSIS for CG 00 Finalloy CG 00 does not make a deposit

Flux Colour - Green

Product of USA